

Marine Maintenance and Repair System

Epo-chem™ RS 500P *and* Epo-chem™ RA 500M



Applying Epo-chem™ RS 500P on a rusty surface



Applying Epo-chem™ RA 500M on a wet surface

- Solvent-free
- Wet & rust tolerant
- Surface preparation standard as low as St 2 & WJ-4
- Universal system for all areas of the ship
- No grit blasting requirements
- No extensive requirements for dehumidification or ventilation
- No humidity or dew point restrictions
- Compatible with all existing ballast tank coatings, including coal-tar epoxies
- Compatible with all shop primers
- No recoating limitations
- Perfectly suited for crew and riding squads application
- Dry-dock, quayside and voyage repairs
- IMO PSPC approved for Sea Water Ballast Tanks
- IMO PSPC-COT approved for Crude Oil Cargo Tanks
- Lloyds Class 1 approval for maintenance and repair
- NSF Certified for Potable Water Applications
- FDA Approved for Food Contact and Potable Water Applications
- Huge cost savings with 5 - 10 year guarantee
- Convenient 5 kgs pack size

Rev: August 2017

East Shawhead Industrial Estate
Coatbridge ML5 4XD
Scotland United Kingdom
Tel: +44 (0) 1236 606060
Fax: +44 (0) 1236 606070
Email: sales@chemcoint.com
Web Site: www.chemcoint.com